

# NEW [WWW.DONGFENG.BE](http://WWW.DONGFENG.BE)

## 22HP



MODEL DF224G3

### MAIN DISPOSITIONS

- Twin turning speeds of-PTO
- Mid-PTO
- Power steering
- Safe start switch
- Fiberglass hood
- Combination meter
- Quality seat system
- Seat belt
- Shuttle synchrony gearbox
- Folding ROPS
- Wide AG Tire

### OPTIONS

- Sun shade
- AG Tire
- Turf Tire
- Industrial Tire

Importateur / Invoeder :

**sprl DURANT**

**48, rue de la Gendarmerie  
B-5600 Philippeville**

**Tél. 071 66 74 92**

**[sprldurant@sprldurant.be](mailto:sprldurant@sprldurant.be)**

# DONGFENG BRAND TRACTOR SERIES

## DF224G3

Tractor Parameters	Model		DF224G3	
	Drive Type		4WD	
	Overall Dimensions L X W X H ( mm )		3231X1388X2321 (Height to steering wheel)	
	Wheel Track	Front	1000	
		Rear	886,1114	
	Wheel Base ( mm )		1547	
	Ground Clearance ( mm )	Under front axle	255	
	Rated Traction Force ( N )		5880	
	Construction Mass ( kg )		1780	
	Min. Turning Radius ( m )		1.789	
	Theoretical Speed ( km/h )	Forward	1.52, 2.02, 3.04, 5.14, 5.90, 7.83, 11.79, 19.91	
Reverse		1.53, 2.03, 3.06, 5.17, 5.94, 7.88, 11.86, 20.04		
Engine Specifications	Model		3M78	
	Type		Vertical, 3-cylinder, in-line cylinder arrangement, radiator cooling, 4-stroke cycle, swirl chamber	
	12-hour Rated Power ( kW/hp )		16.4/22	
	Rated Speed ( rpm )		2600	
	Bore X Stroke ( mm )		78X78.4	
	Total Displacement ( L )		1.123	
Drive System	Clutch		Single action	
	Gearbox		Shuttle synchrony gearbox	
	Main Drive		One pair of spiral bevel gears	
	Differential		Bevel gear	
	Differential Lock		Jaw lock	
	Final Transmissions		Spur gear	
Travelling Mechanism	Tyre	Front	6.00-12 22X7-12	
		Rear	9.5-24 10.5/80-18	
	Steering Gear		Hydraulic steering gear	
	Brake		Wet disk brake	
Working Device	Hydraulic System	Lifting capacity at 610 mm behind lift point (kg)	432kg	
		3-point suspension	Category:I	
	P.T.O.Shaft	Rotating Speed ( rpm )	Rear	540/1000
			Mid	2000
		Spline size	Rear	6-Ø35 Rectangular spline
Mid			11-tooth involate spline	